

Grease sep. in 3m³tank with sludge trap

Grease sep. in 3m³tank

H1	1209	1209
H2	371	371
H3	1139	1139
H4 a	690	690
b	790	790
c	890	890
D1	$\varnothing 1427$	$\varnothing 1427$
D2	$\varnothing 160$	$\varnothing 160$
L1	2258	2258
L2	674	674
L3	674	674

Volume and capacity

	With sludge trap	Without sludge trap
Nominal size	NS7	NS9
Effective volume	1680 l	2290 l
Grease storage capacity	280 l	380 l
Effective volume sludge trap	590 l	~
Max flow rate grease sep.	7 l/s	9 l/s

Part list

1	Inlet pipe
2	Separation plate Sludge trap
3	Outlet pipe
4	Maintenance shaft

GEW.5

GEW.6

GEW.3

GEW.4

GEW.1

GEW.2


Status:



BEHOORT BIJ TEK.

AMERIKAANSE PROJECTIE

BIJBEHORENDE TEK.



BENAMING : Grease separator NS7 / NS9

DATUM : 1-12-2009

SCHAAL : UNITS MM

GETEK. : M. Schouten

PIPELIFE NEDERLAND B.V. POSTBUS 380 1600 AJ ENKHUIZEN

TEL: 0228-355555 TELEFAX 0228-355666

TEK.NR. : 046-011377

A4