

Oil sep. NS3 with sludge trap and ACD

*class I*

Oil sep. NS3 with sludge trap and ACD

*class II*

H1	1439	1439
H2	391	391
H3	1339	1339
H4		
a	749	749
b	849	849
c	949	949
D1	1720	1720
D2	110	110
L1	3132	3132
L2	841	841
L3	1331	1331

**Volume and capacity**

Nominal size	NS3 <i>class I</i>	NS3 <i>class II</i>
Effective volume	3766 L	3784 L
Oil storage capacity	>400 L	>400 L
Effective volume sludge trap	>1200 L	>1200 L
Max flow rate oil sep	3 l/s	3 l/s
Max flow rate bypass	~	~

**Part list**

1	Inlet pipe	
2	Separation plate Sludge trap	
3	Level sensors	(Optional)
4	Oil skimming pipe $\phi 160$	
5	Maintenance shaft	
6	Filter blocks	
7	Outlet pipe with optional ACD (Automatic Closure Device)	

REV.5

REV.6

REV.3

REV.4

REV.1

REV.2


Status:



BELONGS TO DWG

AMERICAN PROJECTION

PART OF DWG



NAME : Oil separator NS3 with sludge trap

DATE : 1-12-2009

SCALE : UNITS MM

DRAWN : M. Schouten

PIPELIFE CORPORATE R&D, FLEVOLAAN 7 1601 MA ENKHUIZEN, THE NETHERLANDS

DWG NO : 046-011368

A4