

Oil sep. NS3 with ACD		<i>class I</i>	Oil sep. NS3 with ACD	<i>class II</i>
H1	1178		1178	
H2	a	653	653	
	b	753	753	
	c	853	853	
H3	1108		1108	
H4	469		469	
D1	Ø1427		Ø1427	
D2	Ø110		Ø110	
L1	2497		2497	
L2	708		708	
L3	879		879	

Volume and capacity

Nominal size	NS3 <i>class I</i>	NS3 <i>class II</i>
Effective volume	2557 l	2595 l
Oil storage capacity	350 l	>350 l
Effective volume sludge trap	~	~
Max flow rate oil sep	3 l/s	3 l/s
Max flow rate bypass	~	~

Part List

1	Inlet pipe	
2	Level sensors	(Optional)
3	Oil skimming pipe Ø160	
4	Maintenance shaft	
5	Filter blocks	
6	Outlet pipe with optional ACD (Automatic Closure Device)	

REV.5	REV.6
REV.3	REV.4
REV.1	REV.2


Status:



BELONGS TO DWG

AMERICAN PROJECTION

PART OF DWG



NAME : Oilseparator NS3

DATE : 1-12-2009

SCALE : UNITS MM

DRAWN : M. Schouten

PIPELIFE CORPORATE R&D, FLEVOLAAN 7 1601 MA ENKHUIZEN, THE NETHERLANDS

DWG NO : 046-011366 A4