

Oil sep. NS6 with ACD

class I

Oil sep. NS6 with ACD

class II

H1	1175	1175
H2 a	655	655
b	755	755
c	855	855
H3	1105	1105
H4	472	472
D1	$\phi 1427$	$\phi 1427$
D2	$\phi 125$	$\phi 125$
L1	2389	2389
L2	701	701
L3	778	778

Volume and capacity

Nominal size	NS6 class I	NS6 class II
Effective volume	2525 l	2595 l
Oil storage capacity	350 l	>350 l
Effective volume sludge trap	~	~
Max flow rate oil sep	6 l/s	6 l/s
Max flow rate bypass	~	~

Part list

1	Inlet pipe	
2	Level sensors	(Optional)
3	Oil skimming pipe $\phi 160$	
4	Maintenance shaft	
5	Filter blocks	
6	Outlet pipe with optional ACD (Automatic Closure Device)	

GEW.5

GEW.6

GEW.3

GEW.4

GEW.1

GEW.2


Status:



BEHOORT BIJ TEK.

AMERIKAANSE PROJECTIE

BIJBEHORENDE TEK.



BENAMING : Oil separator NS6

DATUM : 1-12-2009

SCHAAL : UNITS MM

GETEK. : M. Schouten

PIPELIFE NEDERLAND B.V. POSTBUS 380 1600 AJ ENKHUIZEN

TEL: 0228-355555 TELEFAX 0228-355666

TEK.NR. : 046-011370

A4