

Versatile photovoltaic connection systems

ELECTRICAL
INSTALLATIONS

PHOTOVOLTAIC
CONNECTION SYSTEMS

PIPELIFE 




Mix and match for
optimal installations

Optimize your photovoltaic installation

Save time, materials and effort when installing photovoltaic (PV) systems with connections tailored to your specific project requirements.

We offer a comprehensive selection of high-quality PV installation components: Choose from flexible, UV-resistant and prewired conduits as well as a wide assortment of accessories for streamlined installation processes and bespoke setups.







Application areas

Commercial and residential buildings

Flat and pitched roofs

New-build and renovation projects

Flexible prewired DC conduits

Choose our flexible prewired DC conduits for faster, easier installations.

- + No manual cable feeding
- + Lower transport costs
- + Less waste
- + Various prewiring options


Rigid UV-resistant conduits

Our UV-resistant conduits are complemented by a full range of UV-resistant fittings and accessories, providing complete and consistent protection across your entire photovoltaic setup.

- + Optimal routing
- + Easy, low-friction cable feeding
- + Superior UV resistance
- + Long service life

Conduits

Prewired flexible conduits



	Ø	Packaging	UV resistant	Halogen free	Impact resistant
Cca 2xSOLAR 4 mm ²	25 mm	Coil 100 m	x	x	x
Cca 2xSOLAR 4 mm ² + 1G4 mm ²	25 mm	Coil 100 m	x	x	x
Cca 2xSOLAR 4 mm ² + 1G6 mm ²	25 mm	Coil 100 m	x	x	x
Cca 4xSOLAR 4 mm ² + 1G4 mm ²	32 mm	Coil 100 m	x	x	x
Cca 2xSOLAR 4 mm ²	25 mm	Reel 200 m	x	x	x
Cca 2xSOLAR 4 mm ² + 1G4 mm ²	25 mm	Reel 200 m	x	x	x
Cca 2xSOLAR 4 mm ² + 1G6 mm ²	25 mm	Reel 200 m	x	x	x
Cca 2xSOLAR 6 mm ²	25 mm	Coil 100 m	x	x	x
Cca 2xSOLAR 6 mm ² + 1G6 mm ²	25 mm	Coil 100 m	x	x	x
Cca 4xSOLAR 6 mm ² + 1G6 mm ²	32 mm	Coil 100 m	x	x	x

Empty flexible conduits with pull wire



Ø	Packaging	UV resistant	Halogen free	impact resistant	Low friction
16 mm	coil 100 m	x	x	x	x
20 mm	coil 100 m	x	x	x	x
25 mm	coil 100 m	x	x	x	x
32 mm	coil 100 m	x			

Rigid conduits



Ø	Length	UV resistant	Impact resistant	Low friction
16 mm	3 m	x	x	x
20 mm	3 m	x	x	x
25 mm	3 m	x	x	
32 mm	3 m	x	x	
40 mm	3 m	x	x	
50 mm	3 m	x	x	

Accessories

Couplers



Ø	Packaging	UV resistant	Impact resistant
16 mm	500 pcs	x	x
20 mm	500 pcs	x	x
25 mm	100 pcs	x	x
32 mm	75 pcs	x	x
40 mm	50 pcs	x	x
50 mm	25 pcs	x	x

Bends



Ø	Packaging	UV resistant	Impact resistant
16 mm	100 pcs	x	x
20 mm	100 pcs	x	x
25 mm	50 pcs	x	x
32 mm	1 pc	x	x

End caps



Ø	Packaging	UV resistant	Impact resistant
16 mm	1000 pcs	x	x
20 mm	1000 pcs	x	x
25 mm	500 pcs	x	x

Clips



Ø	Packaging (inner / outer carton)	UV resistant	Impact resistant
16 mm	150 / 1200 pcs	x	x
20 mm	100 / 800 pcs	x	x
25 mm	75 / 600 pcs	x	x
32 mm	40 / 320 pcs	x	x
40 mm	25 / 200 pcs	x	x
50 mm	10 / 80 pcs	x	x



The contents and information contained in this brochure are intended for general marketing purposes only and shall not be relied upon by any person as complete or accurate. In particular, this brochure cannot replace proper expert advice on the characteristics of the products, their usage, suitability for any intended purpose, or the proper processing method. All contributions and illustrations in this brochure are subject to copyright. Unless explicitly otherwise stated, the repetition of content is not permitted. The use of photocopies from this brochure is for private and non-commercial use only. Any duplication or distribution for professional purposes is strictly forbidden. Non-Liability: PIPELIFE has established this brochure to the best of its knowledge. PIPELIFE cannot accept any liability suffered or incurred by any person resulting from or in connection with any reliance on the content of or the information contained in this brochure. This limitation applies to all loss or damage of any kind, including but not limited to direct or indirect damages, consequential or punitive damages, frustrated expenses, lost profit or loss of business.

Date issued: April 2025

Pipelife International GmbH, Wienerbergerplatz 1, 1100 Vienna
T +43 1 602 2030 0, **E** info@pipelife.com, pipelife.com